

MANROSE®

Manufacturers of Ventilation Fans and Equipment

Ducting Catalogue



15

issue

MANROSE®



Manrose Manufacturing continues to maintain its position at the forefront of the ventilation and fan equipment market. The company has been manufacturing practical, reliable ventilation equipment for over 25 years and credits its success to a simple philosophy of offering cost-effective, innovative products to suit any requirement.

Manrose's research and development team has consistently produced products that stand out from the rest, bringing them to market through a team of experienced professionals who understand the needs of our customers. Our policy of ongoing investment in product development has been a key force in driving the company to the top of the ventilation fans and equipment market.

The 2000m² head office complex is divided into administrative, sales and assembly areas, and is responsible for logistics on an ever-growing product range of over 2000 items. In addition to the established 4000m² manufacturing facility in Reading, Manrose have opened a new distribution centre close by.

Thanks to an understanding of local needs and standards, Manrose are able to design products that are ideally suited to UK installers and fully compliant with the latest legislation. And that commitment to quality has also enabled us to make highly profitable inroads into the Far Eastern markets, reversing the general trend and creating more exports for the UK. This is clear evidence that the benefits of innovative design, ease of installation, energy efficiency and sensible pricing we bring to the UK market are also appreciated further afield.

At the heart of Manrose's operation is a total commitment to the UK market, evidenced by the ongoing expansion of manufacturing facilities. Our production facility is fully operational and we operate 27 state-of-the-art moulding machines, ranging from 25 tonnes to 450 tonnes. Our capabilities also include three extrusion machines for flat channel ducting, as well as five machines for the production of PVC and aluminium foil ducting.

A sealed cooling system for the machinery allows the facility to operate 24 hours a day, developing and manufacturing new families of fans encompassing domestic, commercial and industrial applications. As does the fully automated drying and material feed system, the automatic colour dosing system and the state of the art conveyor system that delivers moulding to a central position for sorting, checking and packing.

Also impressive is the electronic assembly system, where dedicated teams work together in assembling equipment with great skill in a positive working environment.

With locations close to the M4 at Slough and Reading, our fleet of vehicles provides fast access to the country's main arteries, ensuring quick delivery from our extensive warehouses, where we hold four weeks of stock at any one time.

Manrose's innovations are the result of listening to customers and understanding their needs. With energy efficiency now a prime consideration, and often compulsory for new buildings, we have ensured that all of our products offer optimum performance, as well as introducing added value features such as the humidistat controlled fan.

The humidistat fan is controlled in relation of humidity levels in the space rather than a pre-set run time. This ensures that the space is thoroughly ventilated without wasting energy through over-ventilating. Similar efficiency improvements are afforded by our occupancy-controlled fans, which switch off when the space has been vacated for a pre-set time. In enabling fans to interact with their environment in this way, Manrose provides end users with a high level of comfort with minimal cost of ownership.



Ducting - Insulated

DUCTING - INSULATED



WHAT IS CONDENSATION?

Condensation is when water vapours make contact with a cold surface and form into liquid, the opposite of evaporation.

Condensation is a serious problem which affects millions of households in the UK.

- Condensation can cause mould and damp, which could lead to serious health risks and affect general wellbeing; asthma, bronchitis and various other respiratory problems
- Can cause wallpaper to peel
- Can contribute to severe structural damage (wood rot & damp)

HOW DO I PREVENT CONDENSATION?

Condensation and damp can be reduced and controlled if you change the habits implemented within your home.

- Washed clothes should be dried outdoors
- Keep doors to bathrooms shut to avoid moisture getting to other parts of the house
- When cooking, cover pots and pans
- Ensure adequate mechanical ventilation (extractor fans)
- Tumble driers should be vented to the atmosphere

HOW WOULD INSULATED DUCTING PROTECT MY HOME?

Ducting in most cases is located within cold, unheated areas of the home, and in most cases not insulated!

Insulated Ducting:

- Retains ambient temperature of room thus preventing steam condensing back into water
- Stops condensed water from dripping back into the property
- Can prevent escalation of structural damage
- Is ideal for vertical installations

Complies with the Domestic Ventilation Compliance Guide.




Ducting - Terminations

Wall Grilles available in White, Grey, Brown, Cotswold Stone and Terracotta. Please state colour.

Gravity Shutter Grille


Round Spigot - External Wall Grille



Cat. No.	Product Type	Size
1161	140 x 140mm Gravity Shutter Grille	100mm/4"
1180	160 x 160mm Gravity Shutter Grille	125mm/5"
1200L	180 x 180mm Gravity Shutter Grille	150mm/6"
1209FG	286 x 286mm Gravity Shutter Grille	230mm/9"
1206FG	362 x 362mm Gravity Shutter Grille	300mm/12"

Gravity Shutter Grille

Rectangular Spigot - External Wall Grille



Cat. No.	Product Type	Size
41010	140 x 140mm Gravity Shutter Grille	110 x 54mm

Weather Proof Cowled Wall Outlet


With Damper - Round Spigot



Cat. No.	Product Type	Size
1240L	Vent Hoods/Weatherproof Cowls	100mm/4"
1241	Vent Hoods/Weatherproof Cowls	125mm/5"
1242	Vent Hoods/Weatherproof Cowls	150mm/6"

Cowled Wall Outlet


With Damper - Rectangular Spigot



Cat. No.	Product Type	Size
41030	145 x 153mm Cowl with Damper	110 x 54mm

Fixed Louvre Grille

Rectangular Spigot



Cat. No.	Product Type	Size
41050	140 x 140mm Fixed Louvre Grille	110 x 54mm

Fixed Louvre Grille

External Wall Grille - Round Spigot




Cat. No.	Product Type	Size
1151	140 x 140mm Fixed Louvre Grille	100mm/4"
1170L	160 x 160mm Fixed Louvre Grille	125mm/5"
1190L	180 x 180mm Fixed Louvre Grille	150mm/6"
12098*	286 x 286mm Fixed Louvre Grille	200mm/8"
1209*	286 x 286mm Fixed Louvre Grille	230mm/9"
1206*	362 x 362mm Fixed Louvre Grille	300mm/12"

*Available in White only

Egg Crate Grille


Round Spigot - External Wall Grille



Cat. No.	Product Type	Size
1145L	140 x 140mm Egg Crate Grille	100mm/4"
1147L	160 x 160mm Egg Crate Grille	125mm/5"
1148L	180 x 180mm Egg Crate Grille	150mm/6"

Egg Crate Grille


Square Spigot - External Wall Grille



Cat. No.	Product Type	Size
1146	140 x 140mm Egg Crate Grille	110 x 54mm

Plate Grilles*

External Plate Wall Grilles




Cat. No.	Product Type	Size
1210L	200 x 200mm Grille Fixed Louvre	150mm/6"
1220L	200 x 200mm Grille Gravity Shutters	150mm/6"
1208	286 x 286mm Grille Fixed Louvre	230mm/9"
1207	362 x 362mm Grille Fixed Louvre	300mm/12"

* Available in White only

Multi Spigot Grille


98mm to 125mm spigot



Cat. No.	Product Type	Size
1221L	Fixed Louvre	98-125mm
1222L	Gravity Shutter	98-125mm

Multi Fit Grilles

Dual fitting for Round and Rectangular Ducting



Cat. No.	Product Type	Size
41051	A-Fixed Louvre - dual fitting	100mm/4"
41011	B-Gravity Shutters - dual fitting	100mm/4"
41031	C-Cowled Outlet - dual fitting	100mm/4"
41052	D-Egg Crate - dual fitting	100mm/4"

Mushroom Cowl

Wall Outlet - Round Spigot



Cat. No.	Product Type	Size
41705	Cowled Outlet	100mm/4"

Fly Screen*

For fixed Wall Grilles



Cat. No.	Product Type	Size
FS100	Fly Screen	100mm/4"
FS120	Fly Screen	120mm/5"
FS150	Fly Screen	150mm/6"

*We don't recommend the use of flyscreens with mechanical extract ventilation. It can reduce the fans performance by upto 60% leaving the fan no longer complying with the building regulation doc Part F & L. Only for use with static-vent and return air boxes.

For information please contact our technical dept.

Internal Door Ventilator

Plastic Fixed Vent



Cat. No.	Product Type	Product Size
41450	Internal Door Ventilator	417x77mm

Circular Soffit Vent

Plastic Fixed Vent



Cat. No.	Product Type	Size
1860W	White	70mm
1860B	Brown	70mm

Ducting - Terminations

Adjustable Vent


PVC Fully Adjustable Vent



Cat. No.	Product Type	Size
1800	PVC Adjustable Vent	229x76mm
1810	PVC Adjustable Vent	229x152mm
1820	PVC Adjustable Vent	229x229mm
1800C	Chrome Plated Vent	229x76mm
1810C	Chrome Plated Vent	229x152mm
1820C	Chrome Plated Vent	229x229mm

Fixed Louvre Vent

PVC Vent for Maximum Flow



Cat. No.	Product Type	Size
1830	Fixed Louvre Vent	229x76mm
1840	PVC Fixed Louvre Vent	229x152mm
1850	PVC Fixed Louvre Vent	229x229mm
1830C	Chrome Plated Fixed Louvre Vent	229x76mm
1840C	Chrome Plated Fixed Louvre Vent	229x152mm
1850C	Chrome Plated Fixed Louvre Vent	229x229mm

Internal Circular Grilles 100mm 4"



Cat. No.	Product Type	Size
2100W	Circular Grilles - White	100mm/4"
2100C	Circular Grilles - Chrome	100mm/4"

Internal Circular Grilles 120mm 5"



Cat. No.	Product Type	Size
2120W	Circular Grilles - White	120mm/5"
2120C	Circular Grilles - Chrome	120mm/5"

Internal Circular Grilles 150mm 6"



Cat. No.	Product Type	Size
2150W	Circular Grilles - White	150mm/6"
2150C	Circular Grilles - Chrome	150mm/6"

External Round Louvred Grilles



Cat. No.	Product Type	Size
41020	Round Louvred Grille	100mm/4"
51020	Round Louvred Grille	125mm/5"
61020	Round Louvred Grille	150mm/6"

Circular Air Diffusers

Duct Valves with Spring Connection & Fully Adjustable Centre Disc



Cat. No.	Product Type	Size
1250	Duct Valves with Spring Connection	100mm/4"
1251	Duct Valves with Spring Connection	120mm/5"
1260	Duct Valves with Spring Connection	150mm/6"
1259	Duct Valves with Spring Connection	200mm/8"

Extract Ventilation Pipes



Weathering Collar

Cat. No.	Product Type	Size
1420	Extract Ventilation Pipes	110mm


Extract Cover



Roof Cowl for Extract Ventilation Pipes

Cat. No.	Product Type	Size
1430	Extract Cover	110mm

Through Roof Vent Kit



Complete with Weathering Slate, 100mm Roof Cowl and 500mm of Soil Pipe

Cat. No.	Product Type	Size
1380	110mm Angled 457x457	110mm
1390	110mm Flat 406x406	110mm

Weathering Slates - Aluminium



Cat. No.	Product Type	Size
1400	110mm Angled 457x457	110mm
1410	110mm Flat 406x406	110mm

Five in One Roof Vent Kit



500 x 500mm lead through roof 5 way ventilation terminal available in dark grey

Cat. No.	Product Type	Size
1395	Duct Sizes 100/110/125/150/160	150/160mm

Ducting - Rectangular


Flat Channel Ducting



Cat. No.	Product Type	External Dimensions			Resistance (Pa) at flow rate								
		H	W	D	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s	
40100	110 x 54mm - L1000mm	54	110	1000	0.8	1.6	3.5	6.0	9.2	13.1	17.1	21.1	
40150	110 x 54mm - L1500mm	54	110	1500	1.2	2.4	5.3	9.1	13.9	19.8	25.9	32	
58100	150 x 70mm - L1000mm	70	150	1000	-	-	-	-	-	-	-	-	
58150	150 x 70mm - L1500mm	70	150	1500	-	-	-	-	-	-	-	-	
58030	150 x 70mm - L300mm	70	150	300	-	-	-	-	-	-	-	-	
58040	150 x 70mm - L400mm	70	150	400	-	-	-	-	-	-	-	-	
55100	204 x 60mm - L1000mm	60	204	1000	<1	<1	<1	1.5	2.2	3.0	3.9	5.1	
55150	204 x 60mm - L1500mm	60	204	1500	<1	<1	1.3	2.2	3.3	4.5	5.9	7.8	
Cat. No.	Product Type	H	W	D	60 l/s			120 l/s			180 l/s		
60910	220 x 90mm - L1000mm	90	220	1000	0.9			3.2			6.7		
60915	220 x 90mm - L1500mm	90	220	1500	1.4			4.9			10.2		
1501	225 x 25mm - L1000mm	25	225	1000	-			-			-		
1503	225 x 25mm - L1500mm	25	225	1500	-			-			-		
1502	225 x 25mm - L2000mm	25	225	2000	-			-			-		
1500	225 x 25mm - L2400mm	25	225	2400	-			-			-		
1509	300 x 25mm - L1000mm	25	300	1000	-			-			-		
1508	300 x 25mm - L1500mm	25	300	1500	-			-			-		
1510	300 x 25mm - L2000mm	25	300	2000	-			-			-		
1515	300 x 25mm - L2400mm	25	300	2400	-			-			-		

Horizontal 90° Bend

Rectangular Horizontal Bend with Female Fittings Suitable for above Kitchen cupboards



Cat. No.	Product Type	External Dimensions			Resistance (Pa) at flow rate								
		H	W	D	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s	
40500	110x54mm	60	152	152	2.3	9.9	21	38	64	93	124	162	
58500	150 x 70mm	-	-	-	-	-	-	-	-	-	-	-	
55500	204 x 60mm	65	260	260	0.7	1.7	4.1	8.4	13	18	25	34	
Cat. No.	Product Type	H	W	D	60 l/s			120 l/s			180 l/s		
60950	220 x 90mm	95	250	250	9			36			80		
1540	225 x 25mm	-	-	-	-			-			-		
1550	300 x 25mm	-	-	-	-			-			-		

Horizontal 45° Bend

Rectangular Horizontal Bend with Female Fittings Suitable for above Kitchen cupboards



Cat. No.	Product Type	External Dimensions			Resistance (Pa) at flow rate								
		H	W	D	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s	
40450	110 x 54mm	-	-	-	-	-	-	-	-	-	-	-	
55810	204 x 60mm	65	240	260	0.2	0.7	1.2	2.1	3.8	6.1	9.2	13	
Cat. No.	Product Type	H	W	D	60 l/s			120 l/s			180 l/s		
60953	220 x 90mm	95	240	200	5			20			46		
1560	225 x 25mm	-	-	-	-			-			-		
1570	300 x 25mm	-	-	-	-			-			-		

Adjustable Horizontal Bend


For connecting to Flat Channel Ducting



Cat. No.	Product Type	External Dimensions			Resistance (Pa) at flow rate								
		H	W	D	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s	
54500	204 x 60mm	-	-	-	-	-	-	-	-	-	-	-	

Vertical 90° Bend


90° Rectangular Vertical Bend with Female Fittings suitable for above Kitchen cupboards



Cat. No.	Product Type	External Dimensions			Resistance (Pa) at flow rate								
		H	W	D	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s	
40600	110 x 54mm	95	115	95	3.3	15.5	36	61	96	138	190	253	
58600	150 x 70mm	-	-	-	-	-	-	-	-	-	-	-	
55600	204 x 60mm	115	210	115	1.1	2.5	5.2	9.8	16.1	24	33.6	45	
Cat. No.	Product Type	H	W	D	60 l/s			120 l/s			180 l/s		
60960	220 x 90mm	117	224	120	7			28			66		
1600	225 x 25mm	-	-	-	-			-			-		
1610	300 x 25mm	-	-	-	-			-			-		


Ducting - Rectangular

45° Vertical Bend



Cat. No.	Product Type	External Dimensions			Resistance (Pa) at flow rate								
		H	W	D	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s	
40045	110 x 54mm	-	-	-	-	-	-	-	-	-	-	-	-
55645	204 x 60mm	-	-	-	-	-	-	-	-	-	-	-	-
Cat. No.	Product Type	H	W	D	60 l/s		120 l/s		180 l/s				
60963	220 x 90mm	110	225	115	6		27		65				
1670	225 x 25mm	-	-	-	-		-		-				
1690	300 x 25mm	-	-	-	-		-		-				

Horizontal T-Piece - Adaptor to Connect Flat Channel Ducting




Cat. No.	Product Type	Size	Resistance (Pa) at flow rate							
			8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s
40080	110 x 54mm	110 x 54mm	vary on installation							
55582	204 x 60mm	204 x 60mm	vary on installation							

Cross Over Duct Connector




Cat. No.	Product Type	External Dimensions			Resistance (Pa) at flow rate							
		H	W	D	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s
44273	30° Drop Down Connection	120	220	210	0.2	0.5	1.7	3.6	6.0	9.1	12.4	16.6

Rectangular Wall Plate




Cat. No.	Product Type	External Dimensions			Resistance (Pa) at flow rate								
		H	W	D	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s	
41150	154 x 154mm	154	154	-	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
58650	172 x 172mm	172	172	-	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
51150	119 x 264mm	119	264	-	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a

Flat Channel Connector



Cat. No.	Product Type	External Dimensions			Resistance (Pa) at flow rate							
		H	W	D	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s
40200	110 x 54mm	54	114	100	<1	<1	1.1	1.4	2.2	3.4	4.8	6.4
58200	150 x 70mm	-	-	-	-	-	-	-	-	-	-	-
55200	204 x 60mm	64	212	100	<1	<1	<1	<1	<1	<1	1.2	1.5
1520	225 x 25mm	-	-	-	-	-	-	-	-	-	-	-
1530	300 x 25mm	-	-	-	-	-	-	-	-	-	-	-
Cat. No.	Product Type	H	W	D	60 l/s		120 l/s		180 l/s			
60920	220 x 90mm	95	224	52	<1		<1		<1			

Flat Channel Connector with Internal Damper



Cat. No.	Product Type	External Dimensions			Resistance (Pa) at flow rate							
		H	W	D	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s
40270	110 x 54mm - with Damper	60	115	75	16	17.5	19.5	22	25.5	30.5	36	42

Rigid Duct Attenuator



Cat. No.	Product Type	Size	Resistance (Pa) at flow rate									
			8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s		
SL55105	0.6m Length	204 x 60mm	<1	<1	2.3	4.2	-	-	-	-	-	12.2
SL55100	1.0m Length	204 x 60mm	<1	<1	2.2	4.1	-	-	-	-	-	15

Insulated Rectangular Duct



Cat. No.	Product Type	Size	Resistance (Pa) at flow rate									
			8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s		
IJRP55150	1.5m Length	204 x 60mm	<1	<1	1.3	2.2	3.3	4.5	5.9	7.8	-	-
IJRP55020	2.0m Length	204 x 60mm	-	-	-	-	-	-	-	-	-	-
IJRP60915	1.5m Length	220 x 90mm	-	-	-	-	-	-	-	-	-	-

Insulated Vertical Bend

Cat. No.	Product Type	Size	Resistance (Pa) at flow rate									
			8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s		
IJBV55645	Vertical 45° Bend	204 x 60mm	0.1	0.5	1.3	2.5	4.4	6.9	10	13.3	-	-
IJBV55600	Vertical 90° Bend	204 x 60mm	1.1	2.5	5.2	9.8	16.1	24	33.6	45	-	-

Insulated Horizontal Bend



Cat. No.	Product Type	Size	Resistance (Pa) at flow rate									
			8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s		
IJBH55810	Horizontal 45° Bend	204 x 60mm	0.2	0.7	1.2	2.1	3.8	6.1	9.2	13	-	-
IJBH55500	Horizontal 90° Bend	204 x 60mm	0.7	1.7	4.1	8.4	13	18	25	34	-	-
Cat. No.	Product Type	Size	60 l/s		120 l/s		180 l/s					
IJBH60950	Horizontal 90° Bend	220 x 90mm	9		36		80					

Insulated T-Piece Bend




Cat. No.	Product Type	Size	Resistance (Pa) at flow rate							
			8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s
IJTH55582	T-Piece	204 x 60mm	vary on installation							

Ducting - Adaptors

Elbow 90° Bend M to F


Connector for joining Round Pipe, Flexi Hose & Flat Channel Ducting



Cat. No.	Product Type	External Dimensions			Resistance (Pa) at flow rate								
		H	W	D	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s	
40300	100mmØ to 110 x 54mm	90	115	140	3	8	17.7	33	49.9	74.5	101	137	
58400	125mmØ to 150 x 70mm	-	-	-	-	-	-	-	-	-	-	-	
54400	100mmØ to 204 x 60mm	80	215	195	2.9	7.1	15.1	28	45.1	68.1	92.2	118	
55400	125mmØ to 204 x 60mm	80	215	195	3.1	5.9	12.2	25	43.6	62.2	86	111	
56400	150mmØ to 204 x 60mm	80	215	195	2.8	4.9	11.6	21	31	41	53	67	
60941	100mmØ to 220 x 90mm	118	226	240	-	-	-	-	-	-	-	-	
60951	125mmØ to 220 x 90mm	118	226	240	-	-	-	-	-	-	-	-	
60961	150mmØ to 220 x 90mm	11	226	240	-	-	-	-	-	-	-	-	

Short to Round Rectangular Adaptor

with male/female adaptors for Connecting Flat Channel Ducting to Round Hose



Cat. No.	Product Type	External Dimensions			Resistance (Pa) at flow rate								
		H	W	D	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s	
40700	100mm to 110 x 54mm (F)	60	110	105	1.2	4.3	8.4	20	30.2	43	62	88	
40710	100mm to 110 x 54mm (M)	60	110	105	1.2	4.3	8.4	20	30.2	43	62	88	

Round to Rectangular Adaptor - Adaptor to Connect Flat Channel Ducting



Cat. No.	Product Type	External Dimensions			Resistance (Pa) at flow rate								
		H	W	D	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s	
40701	100mmØ to 110 x 54mm	100	115	180	1.2	4.2	8.3	19.8	29.9	42	60	86	
58701	125mmØ to 150 x 70mm	-	-	-	-	-	-	-	-	-	-	-	
55710	125mmØ to 204 x 60mm	140	210	215	1.0	1.96	3.2	4.9	6.7	8.7	11.2	14.5	
55700	150mmØ to 204 x 60mm	140	210	213	<1	<1	1.5	2.8	4.5	6.7	9	11.5	
60970	150mmØ to 220 x 90mm	160	225	203	-	-	-	-	-	-	-	-	


Adaptor - Adaptor to Connect Round Pipe Ducting



Cat. No.	Product Type	External Dimensions			Resistance (Pa) at flow rate								
		H	W	D	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s	
54544	125mm to 100mm	-	-	-	-	-	-	-	-	-	-	-	

Offset Reducer


Adaptor to Connect Round Pipe Ducting



Cat. No.	Product Type	External Dimensions			Resistance (Pa) at flow rate								
		H	W	D	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s	
45644	150mm to 125mm or 100mm	-	-	-	-	-	-	-	-	-	-	-	

Circular Reducer

Adaptor to Connect Round Pipe Ducting, Flexi Hose & Fan Spigots




Cat. No.	Product Type	External Dimensions			Resistance (Pa) at flow rate								
		H	W	D	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s	
54119	125mm to 100mm	-	-	-	-	-	-	-	-	-	-	-	
65118	150mm to 125mm	-	-	-	-	-	-	-	-	-	-	-	
86117	200mm to 150mm	-	-	-	-	-	-	-	-	-	-	-	
98116	250mm to 200mm	-	-	-	-	-	-	-	-	-	-	-	
12800	300mm to 200mm	-	-	-	-	-	-	-	-	-	-	-	
40419	110mm to 100mm	-	-	-	-	-	-	-	-	-	-	-	

Rubber Spigot Adaptor - Adaptor to Connect Cookerhood Spigots




Cat. No.	Product Type	External Dimensions			Resistance (Pa) at flow rate								
		H	W	D	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s	
50519	120mm to 125mm	-	-	-	-	-	-	-	-	-	-	-	

Plenum Cooker Hood/Fan - with Connector



Cat. No.	Product Type	External Dimensions			Resistance (Pa) at flow rate								
		H	W	D	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s	
1640	100mm	-	-	-	-	-	-	-	-	-	-	-	
1650	100mm	-	-	-	-	-	-	-	-	-	-	-	
1645	120mm	-	-	-	-	-	-	-	-	-	-	-	
1655	120mm	-	-	-	-	-	-	-	-	-	-	-	

Round to Rectangular Adaptor - Requires 414C Connector




Cat. No.	Product Type	External Dimensions			Resistance (Pa) at flow rate								
		H	W	D	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s	
40725	100mm to 225 x 25mm	-	-	-	-	-	-	-	-	-	-	-	
40730	105mm to 300 x 25mm	-	-	-	-	-	-	-	-	-	-	-	



Ducting - Adaptors


Double Airbrick



Cat No.	Product Type	External Dimensions			Resistance (Pa) at flow rate								
		H	W	D	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s	
60905W	220 x 90mm White	145	245	80	0.2	1.6	4.3	8.7	13.9	21.1	27.5	37.4	
60905B	220 x 90mm Brown	145	245	80	0.2	1.6	4.3	8.7	13.9	21.1	27.5	37.4	
60905CS	220 x 90mm Cotswold St.	145	245	80	0.2	1.6	4.3	8.7	13.9	21.1	27.5	37.4	
60905T	220 x 90mm Terracotta	145	245	80	0.2	1.6	4.3	8.7	13.9	21.1	27.5	37.4	

Double Airbrick Adaptor to Rectangular Duct


Fits High Performance Ducting 220 x 90mm to double Airbrick 60905



Cat No.	Product Type	External Dimensions			Resistance (Pa) at flow rate								
		H	W	D	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s	
60977	Double Airbrick Adaptor	-	-	-	-	-	-	-	-	-	-	-	

Double Airbrick Adaptor to Round Duct


Fits 100/125/150mm Round Pipe



Cat No.	Product Type	External Dimensions			Resistance (Pa) at flow rate						
		H	W	D	60 l/s		120 l/s		180 l/s		
60954	Double Airbrick Adaptor	-	-	-	-	-	-	-	-	-	-

High Performance Ducting Adaptor


Fits 125 Channel Ducting 220x90mm to High Performance Ducting



Cat No.	Product Type	External Dimensions			Resistance (Pa) at flow rate								
		H	W	D	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s	
60957	Adaptor	-	-	-	-	-	-	-	-	-	-	-	


Airbrick Adaptor

To connect Flat Channel Ducting and Airbrick Ventilators




Cat No.	Product Type	External Dimensions			Resistance (Pa) at flow rate								
		H	W	D	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s	
1580	Adaptor	-	-	-	-	-	-	-	-	-	-	-	
1590	Adaptor	-	-	-	-	-	-	-	-	-	-	-	

Extended Horizontal Airbrick - For 225mm to 300mm System



Cat No.	Product Type	External Dimensions			Resistance (Pa) at flow rate								
		H	W	D	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s	
1572	Fits Direct to Flat Channel	-	-	-	-	-	-	-	-	-	-	-	
1573	Fits Direct to Flat Channel	-	-	-	-	-	-	-	-	-	-	-	

Slimline Airbrick




Cat. No.	Product Type	Size	Resistance (Pa) at flow rate								
			8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s	
45010*	Horizontal Louvre	110x54mm	-	-	-	-	-	-	-	-	
45011	Vertical Louvre	110x54mm	-	-	-	-	-	-	-	-	

* Fits into airbrick adaptor - 40770

Slimline Airbrick

Wall Outlet



Cat. No.	Product Type	Size	Resistance (Pa) at flow rate								
			8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s	
55010	Horizontal Louvre	204x60mm	-	-	-	-	-	-	-	-	
55011	Vertical Louvre	204x60mm	-	-	-	-	-	-	-	-	
55012	Low resistance airbrick	204x60mm	-	-	-	-	-	-	-	-	

Slimline Airbrick with Internal Damper



Cat. No.	Product Type	Size	Resistance (Pa) at flow rate								
			8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s	
58501	Horizontal Louvre	150x70mm	-	-	-	-	-	-	-	-	
55501	Horizontal Louvre	204x60mm	-	-	-	-	-	-	-	-	

Airbrick Adaptor

For use with Flat Channel Ducting and Slimline Air Bricks



Cat. No.	Product Type	Size	Resistance (Pa) at flow rate								
			8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s	
40770	Airbrick Adaptor	110x54mm	-	-	-	-	-	-	-	-	

* Fits airbrick 45010

Ducting - Flexible


Aluminium Flexible Ducting

Aluminium Flexible Ducting Hose



Cat. No.	Product Type	Size
1015	380mm	100mm/4"
1000	1.5 metre	100mm/4"
1010	3 metre	100mm/4"
1016	380mm	120mm/5"
1011	1.5 metre	120mm/5"
1012	3 metre	120mm/5"
1300	380mm	150mm/6"
1013	1.5 metre	150mm/6"
1014	3 metre	150mm/6"

Insulated Round Hose



Cat. No.	Product Type	Size
INSDUCT102	10 metre	102mm
INSDUCT127	10 metre	127mm
INSDUCT152	10 metre	152mm
INSDUCT202	10 metre	202mm
INSDUCT252	10 metre	252mm
INSDUCT317	10 metre	317mm

Aluminium Laminated Flexible Ducting

Aluminium Flexible Hose



Cat. No.	Product Type	Size
1050	102mm Aluduct - 10 metre	100mm 4"
1060	127mm Aluduct - 10 metre	125mm 5"
1070	152mm Aluduct - 10 metre	150mm 6"
1071	200mm Aluduct - 10 metre	200mm 8"
1080	250mm Aluduct - 10 metre	230mm 9"
1090	315mm Aluduct - 10 metre	300mm 12"

Rectangular PVC Flexible Ducting


3m Rectangular Flexible Hose



Cat. No.	Product Type	Size
10212	3 metre - 110 x 54mm	100mm/4"
10255	3 metre - 150 x 70mm	125mm/5"
10252	3 metre - 204 x 60mm	125mm/5"
10263	3 metre - 220 x 90mm	150mm/6"

PVC Flexible Ducting

PVC Flexible Ducting Hose




Cat. No.	Product Type	Size
3761	1 metre	80mm/3"
3763	3 metre	80mm/3"
3766	6 metre	80mm/3"
37615	15 metre	80mm/3"
101025	1 metre	100mm/4"
1020	3 metre	100mm/4"
1024	6 metre	100mm/4"
10415	15 metre	100mm/4"
1023	45 metre	100mm/4"
10251	1 metre	120mm/5"
5753	3 metre	120mm/5"
1030	4 metre	120mm/5"
5756	6 metre	120mm/5"
10515	15 metre	120mm/5"
1068	45 metre	120mm/5"
10253	1 metre	150mm/6"
6763	3 metre	150mm/6"
1040	5 metre	150mm/6"
6766	6 metre	150mm/6"
10615	15 metre	150mm/6"
8781	1 metre	200mm/8"
8783	3 metre	200mm/8"
8786	6 metre	200mm/8"
87815	15 metre	200mm/8"

Ducting - Round

Round Pipes - PVC

Cat. No.	Product Type	Size
41350	100mm - L350	100mm/4"
41500	100mm - L500	100mm/4"
41900	100mm - L1000	100mm/4"
41915	100mm - L1500	100mm/4"
42000	100mm - L2000	100mm/4"
51350	120mm - L350	120mm/5"
51500	120mm - L500	120mm/5"
51900	120mm - L1000	120mm/5"
51915	120mm - L1500	120mm/5"
52000	120mm - L2000	120mm/5"
61350	150mm - L350	150mm/6"
61500	150mm - L500	150mm/6"
61900	150mm - L1000	150mm/6"
61915	150mm - L1500	150mm/6"
62000	150mm - L2000	150mm/6"
40420	4" Round Pipe clip	100mm/4"
50520	5" Round Pipe clip	120mm/5"



Round Sleeve Pipe


Creates Telescopic Assembly with Round Pipe

Cat. No.	Product Type	Size
SPIPE4	Round Pipe Sleeve - 1m	100mm/4"
SPIPE5	Round Pipe Sleeve - 1m	120mm/5"
SPIPE6	Round Pipe Sleeve - 1m	150mm/6"



Round Pipe Telescopic Assembly

Cat. No.	Product Type	Size
TPIPE4	250mm to 450mm	100mm/4"
TPIPE5	250mm to 450mm	120mm/5"
TPIPE6	250mm to 450mm	150mm/6"



Round Pipe Connectors

For use with PVC/Aluminium Ducting


Cat. No.	Product Type	Size
414C	Connector/PVC	100mm/4"
515C	Connector/PVC	120mm/5"
616C	Connector/PVC	150mm/6"
414CD	Connector with Damper	100mm/4"
515CD	Connector with Damper	120mm/5"
616CD	Connector with Damper	150mm/6"
1091	Connector/Aluminium	100mm/4"
1092	Connector/Aluminium	120mm/5"
1093	Connector/Aluminium	150mm/6"
10918	Connector/Aluminium	200mm/8"
10919	Connector/Aluminium	230mm/9"
10912	Connector/Aluminium	300mm/12"



T piece Connectors

PVC/Aluminium to connect Round Ducting

Cat. No.	Product Type	Size
44920	T Piece/PVC	100mm/4"
44930	T Piece/PVC	120mm/5"
44940	T Piece/PVC	150mm/6"
1094	T Piece/Aluminium	100mm/4"
1095	T Piece/Aluminium	120mm/5"
1096	T Piece/Aluminium	150mm/6"
10948	T Piece/Aluminium	200mm/8"
10949	T Piece/Aluminium	230mm/9"
10943	T Piece/Aluminium	300mm/12"



Y piece Connectors

PVC to connect Round Ducting


Cat. No.	Product Type	Size
44950	Y Piece/PVC	100mm/4"
44960	Y Piece/PVC	120mm/5"
44970	Y Piece/PVC	150mm/6"



90° Bend

Connectors for Round Pipe Systems

Cat. No.	Product Type	Size
44900	Connector/PVC/90°	100mm/4"
55900	Connector/PVC/90°	120mm/5"
66900	Connector/PVC/90°	150mm/6"



45° Bend

Connectors for Round Pipe Systems

Cat. No.	Product Type	Size
44450	Connector/PVC/45°	100mm/4"
55450	Connector/PVC/45°	120mm/5"



Threaded Hose Connectors

Hose Connector for Round Pipe system & Flexi Hose

Cat. No.	Product Type	Size
4124M	100mm - Male	100mm/4"
4126F	100mm - Female	100mm/4"
5124M	120mm - Male	120mm/5"
5126F	120mm - Female	120mm/5"
6124M	150mm - Male	150mm/6"
6126F	150mm - Female	150mm/6"



Insulated PVC Round Pipe

Cat. No.	Product Type	Size
IJRP41915	1.5m Length	100mm
IJRP42000	2.0m Length	100mm
IJRP51915	1.5m Length	125mm
IJRP52000	2.0m Length	125mm
IJRP61915	1.5m Length	150mm
IJRP62000	2.0m Length	150mm



Insulated Bend

Cat. No.	Product Type	Size
IJB44450	45° PVC Bend	100mm
IJB44900	90° PVC Bend	100mm
IJB55450	45° PVC Bend	125mm
IJB55900	90° PVC Bend	125mm
IJB66900	90° PVC Bend	150mm



Insulated T-Piece

Cat. No.	Product Type	Size
IJTP44920	T-Piece	100mm
IJTP44930	T-Piece	125mm
IJTP44940	T-Piece	150mm



Round Wall Plate


Cat. No.	Product Type	Size
41140	154 x 154mm	100mm/4"
51140	172 x 172mm	120mm/5"
51145	200 x 200mm	150mm/6"



Condensation Traps

Condensation Trap with Overflow

Cat. No.	Product Type	Size
1440	Condensation Traps	100mm/4"
1450	Condensation Traps	125mm/5"
1460	Condensation Traps	150mm/6"



Ducting - Accessories



Flat Channel Clip

Cat. No.	Product Type	Size
41220	110 x 54mm	110 x 54mm
58220	150 x 70mm	150 x 70mm
51220	204 x 60mm	204 x 60mm



Duct Support Clip

For use with Flat Channel Ducting

Cat. No.	Product Type	Size
60922	Duct support clip	220x90mm
1680	Duct support clip	225x25mm/ 300x25mm



In-Line Backdraught Shutter

Can be mounted onto the spigot of the 4" / 5" / 6" XF, SF fans or In-Line in the ducting

Cat. No.	Product Type	Size
1230	In-Line backdraught Shutter	100mm/4"
1231	In-Line backdraught Shutter	120mm/5"
1232	In-Line backdraught Shutter	150mm/6"




Intake/Extract Mounting Spigot

Cat. No.	Product Type	Size
1307	Inline Ducting Connector For WF230 Series	230mm
13071	Inline Ducting Connector For WF300 Series	300mm



4 Way Spigot Adaptor


Cat. No.	Product Type	Size
1308	For Manrose 230mm Fans	230mm
13081	For Manrose 300mm Fans	300mm



Metal Clamps

Metal Worm Drive Clamps 8mm wide

Cat. No.	Product Type	Size
1100	50mm - 110mm	100mm/4"
1110	60mm - 165mm	120mm/5"
1120	60mm - 325mm	150mm/6"



Tapes

Self Adhesive Tapes

Cat. No.	Product Type	Size
11405W	PVC Tape - White	50mmx5m
1140	PVC Tape - Grey	50mmx10m
1140W	PVC Tape - White	50mmx10m
14033W	PVC Tape - White	50mmx33m
1130	Aluminium Tape	50mmx45m



Roof Cowl Termination Set

Cat. No.	Product Type	Size
1309	For Manrose 230mm Fans	230mm
13091	For Manrose 300mm Fans	300mm



Extension Sleeve

For walls from 380mm (15") to 533mm (21")

Cat. No.	Product Type
COMTK150ES	For 150 Series
COMTK230ES	For 230 Series
COMTK300ES	For 300 Series



Spares

Cat. No.	Product Type
1310	TDI Replacement Timer Boards
1320	HSB Replacement Humidity Timer Board and Sensor
1321	As above but with twin speed Control
1330	Replacement motors
1340	Replacement Pullcord switches
1345	Extra Long Pullcord switches



Extra Long Screws (55mm)


Cat. No.	Product Type
1370	For Fitting Window Fans in double glazed sealed units (3 per pack)
1374	For Fitting Window Fans in double glazed sealed units for 230mm (9") 300mm (12") double glazing screws

Ducting - Kits

Wall Outlets available in White, Grey, Brown, Terracotta & Cotswold Stone - Please state colour when ordering.

Window Vent Kits

Cat. No.	Product Type	Size
1269	Window Vent Kit for XF100 Fans Complete with External Backdraught Shutters	100mm/4"
12691	As above with Fixed Louvre Grille for XF100A Fans	100mm/4"
1267	Window Vent Kit for XF120 Fans Complete with External Backdraught Shutters	120mm/5"
12671	As above with Fixed Louvre Grille for XF120A	120mm/5"
1268	Window Vent Kit for XF150 Fans Complete with External Backdraught Shutters	150mm/6"
12681	As above with Fixed Louvre Grille for XF150A	150mm/6"



Duct Kit

400mm Wall Vent Kit for the WF Series / Aluminium Wall Liner

Cat. No.	Product Type	Size
1300	for WF150 Series	150mm/6"
1301	for WF230 Series	230mm/9"
1299	for WF300 Series	300mm/12"



Wall Vent Kits

Kits complete with Aluminium Flexible Ducting & External Wall Grilles in White, Grey, Brown, Terracotta & Cotswold Stone (380mm length)


Cat. No.	Product Type	Size
1270	XFFK for XF100 range	100mm/4"
1271	XFFK for XF120 range	120mm/5"
1280	SVK for XF150 range	150mm/6"
1290	AVK for XF150A range	150mm/6"
1291	SVK for XFS230 range	230mm/9"
1292	SVK for XFS 300 range	300mm/12"



Tumble Dryer Venting Kit

With Gravity Grille

Cat. No.	Product Type	Size
41703	Tumble Dryer Kit 100mm	100mm/4"



Indoor Tumble Dryer Vent Kit


Cat. No.	Product Type	Size
41704	Tumble Dryer Kit	100mm/4"



Tumble Dryer - Venting Kit

With Cowled Grille



Cat. No.	Product Type	Size
7207	Rectangular Tumble Dryer Kit 100mm	100mm/4"
7208	Round Tumble Dryer Kit 100mm	100mm/4"



Cooker Hood - Venting Kit

With Gravity Grille

Cat. No.	Product Type	Size
43076	Cooker Hood kit 100mm	100mm/4"
43077	Cooker Hood kit 120mm	120mm/5"
43078	Cooker Hood kit 150mm	150mm/6"



High Rise Installation Kit


With Round Cowl Outlet

Cat. No.	Product Type	Size
72447	Round Pipe 100mm	100mm/4"

Telescopic Outlet Set

With Weatherproof Cowl


Cat. No.	Product Type	Size
7108	Round Pipe 250mm to 450mm	100mm/4"
7508	Round Pipe 250mm to 450mm	120mm/5"
7608	Round Pipe 250mm to 450mm	150mm/6"



Telescopic Return Air Box Set

With Fixed Grille


Cat. No.	Product Type	Size
7116	Round Pipe 250mm to 450mm	100mm/4"
7516	Round Pipe 250mm to 450mm	120mm/5"
7616	Round Pipe 250mm to 450mm	150mm/6"



Weatherproof Cowl Kit

1m Round Hose with Weatherproof Cowl


Cat. No.	Product Type	Size
7202	1m Round Hose kit	100mm/4"
7203	1m Round Hose kit	120mm/5"
7204	1m Round Hose kit	150mm/6"



Gravity Grille Kit

1m Round Hose with Gravity Grille


Cat. No.	Product Type	Size
7205	1m Round Hose kit	100mm/4"
7216	1m Round Hose kit	120mm/5"
7217	1m Round Hose kit	150mm/6"



Fixed Grille Kit

1m Round Hose with Fixed Grille


Cat. No.	Product Type	Size
7218	1m Round Hose kit	100mm/4"
7215	1m Round Hose kit	120mm/5"
7220	1m Round Hose kit	150mm/6"



Rectangular Return Air Box

With Fixed Louvre Grille


Cat. No.	Product Type	Size
7117	Rectangular 400mm	110x54mm



Rectangular Return Air Box

With Fixed Louvre Grille


Cat. No.	Product Type	Size
7511	Rectangular 400mm	204x60mm



Rectangular Return Air Box


With Airbrick Outlet

Cat. No.	Product Type	Size
7917	with High performance 400mm Ducting	204x60mm



Ducting - Kits & Radial Systems


Wall Outlets available in White, Grey, Brown, Terracotta & Cotswold Stone - Please state colour when ordering.



Flat Channel Ducting Kit

With Weatherproof Cowl and Horizontal Bend


Cat. No.	Product Type	Size
7212	3m Flat Channel Ducting Kit	100mm/4"
7214	3m Flat Channel Ducting Kit with additional horizontal bend	100mm/4"



Flat Channel Ducting Kit

With Airbrick Outlet and Horizontal Bend


Cat. No.	Product Type	Size
7227	3m Flat Channel Ducting Kit	125mm/5"
7219	3m Flat Channel Ducting Kit with additional horizontal bend	125mm/5"



Round Pipe Ducting Kit

With Cowlled Outlet & 90° Bend


Cat. No.	Product Type	Size
72605	3m Flat Channel Ducting Kit	150mm/6"
72607	3m Round Pipe Ducting Kit with additional horizontal 90° bend	150mm/6"



High Performance Ducting Kit

Flat Channel Ducting Kit

Cat. No.	Product Type	Size
72650	3m Flat Channel Ducting Kit with Cowlled Outlet	150mm/6"



High Performance Ducting Kit

Flat Channel Ducting Kit

Cat. No.	Product Type	Size
72653	3m Round Pipe Ducting Kit with Airbrick outlet	150mm/6"



90° Valve Elbow - Radial System

To connect the Circular Pipe to a supply or extract diffuser

Cat. No.	Product Type	Size
VE75	90° Valve Elbow	75mmØ
VE90	90° Valve Elbow	90mmØ



Circular Pipe - Radial System

For installation in concrete ceilings, suspended ceilings, installation walls, risers or frames

Cat. No.	Product Type	Size
SR7550	Circular Pipe	75mmØ
SR9020	Circular Pipe	90mmØ



Outlet Manifold - Radial System

To control the distribution of Circular Pipe and also to precisely regulate the airflow to each room

Cat. No.	Product Type
MANIFOLD5	Outlet Manifold 5 connections
MANIFOLD10	Outlet Manifold 10 connections



Reducer - Radial System

Cat. No.	Product Type
RFM160150	160mm (F) to 150mm (M)



Manifold Coupling - Radial System

To connect the Circular Pipe to the Manifold Outlet

Cat. No.	Product Type	Size
MC75	Manifold Coupling	75mmØ
MC90	Manifold Coupling	90mmØ



End Plug - Radial System

Cat. No.	Product Type	Size
EP75	End Plug	75mmØ
EP90	End Plug	90mmØ



O-Ring - Radial System

Cat. No.	Product Type	Size
OR75	O-Ring	75mmØ
OR90	O-Ring	90mmØ



Circular Extract Diffuser

Cat. No.	Product Type	Size
1251M	Circular Extract Diffuser	125mmØ








Circular Supply Diffuser

Cat. No.	Product Type	Size
1251MIT	Circular Supply Diffuser	125mmØ


Ducting - Fire Stopping

Fire Seals

For Flat Channel Ducting & Round Pipes


	Cat. No.	Product Type	Size
	FS110D*	Fire seal	110mm
	FS150D*	Fire seal	150mm
	FS204D*	Fire seal	204mm
	FS225D*	Fire seal	225mm
	FS300D*	Fire seal	300mm
	FSC110*	Fire Seal Cage	110mm
	FSC150*	Fire Seal Cage	150mm
	FSC204*	Fire Seal Cage	204mm
	FSC225*	Fire Seal Cage	225mm
	FSC300*	Fire Seal Cage	300mm
	FCR110N*	Rectangular Fire Collar	110x54mm
	FCR204N*	Rectangular Fire Collar	204x60mm
	FCR220N*	Rectangular Fire Collar	225x25mm
	FCR300*	Rectangular Fire Collar	300x25mm
		FCSC100N*	Round fire sleeves
FCSC125N*		Round fire sleeves	125mm
FCSC150N*		Round fire sleeves	150mm
	FCR204X3	Fire Sleeve - 3 sided	204x60

Metal Valves & Metal Fire Valves*

	Cat. No.	Product Type	Size
	1250M	Metal Valves	100mm/4"
	1251M	Metal Valves	125mm/5"
	1260M	Metal Valve (available shortly)	150mm/6"
	FV1250*	Metal Valve rated to 60mins	100mm/4"
	FV1251*	Metal Valve rated to 60mins	125mm/5"
	FV1260*	Metal Valve rated to 60mins	150mm/6"

Fire Dampers

Can be mounted vertically or horizontally, and have a one hour fire rating in both directions



Cat. No.	Product Type	Size
1261*	Fusible Link Fire Damper	100mm/4"
1262*	Fusible Link Fire Damper	120mm/5"
1263*	Fusible Link Fire Damper	150mm/6"

*Manrose Manufacturing Ltd does not guarantee compliance with Building Regulations Part B, Fire Spread or other regulations that relate to fire planning. Suitability to comply with these regulations should be determined prior to installation and in conjunction with Building Control Officers. Compliance with the Regulations is specifically excluded from quotations and designs.

	Minutes Protection	Metal Fire Valves			Round Fire Sleeve			Rectangular Fire Collar			Rectangular Fire Wrap	
		100mm	125mm	150mm	100mm	125mm	150mm	110 x 54	204 x 60	220 x 90	110 x 54	204 x 60
72mm Stud Partition	30											
	60							FCR110N	FCR204N	FCR204X3		
	120											
100mm Stud Partition	30											
	60							FCR110N	FCR204N	FCR204X3		
	120											
130mm Stud Partition	30											
	60				FCSC100N	FCSC100N	FCSC150N	FCR110N	FCR204N	FCR204X3	FSC110	FSC204
	120											
130mm Masonary	30											
	60				FCSC100N	FCSC100N	FCSC150N	FCR110N	FCR204N	FCR204X3	FS110D	FS204D
	120											
140mm Masonary	30											
	60				FCSC100N	FCSC100N	FCSC150N	FCR110N	FCR204N	FCR204X3	FS110D	FS204D
	120											
Ceilings	30											
	60	FV1250	FV1251	FV1260								
	120											

Note: For a copy of the Fire Certificates for the product(s) above, call our Technical Department on 01753 876908

MANROSE®

Manrose Manufacturing Limited
1 Albion Close, Slough,
Berkshire SL2 5DT

Telephone: 01753 691399

Facsimile: 01753 692294

Email: sales@manrose.com

www.manrose.co.uk

Free Fax Order Line: 0800 387646

For further information on any product, please
telephone our Technical Department
Telephone: 01753 876908



ISO 9001 accredited

